



Husqvarna K 3000 Cut-n-Break

Our Cut-n-Break method is the natural choice when you need to cut deep but want a machine with low tool and maintenance costs. The K 3000 Cut-N-Break enables you to cut as deep as 16" from one side. Suitable for flush cutting close to walls and floors as well as for smaller jobs like window openings where you want to avoid overcutting at the corners.




"PULLING" ROTATION

The blade on all of our electric cutters rotates forward, cutting into the material efficiently, minimizing the risk of sticking and kickbacks.



ERGONOMICALLY DESIGNED REAR HANDLE

The convenient design of the rear handle makes operation easier.



FLUSH CUTTING

Adjustable blade guard enables flush cutting



HIGH PERFORMING BLADES INCLUDED

Twin blades, with a very stable core and cutting performance are delivered with the machine.

Features Husqvarna K 3000 Cut-n-Break

- The water adjustment gives efficient dust management and makes operation easier and more efficient.
- A powerful electric cutter for both indoor and outdoor use.
- Ergonomic and easy cutting
- Our anti-vibration system reduces vibrations in the cutter handles, so they are more comfortable to hold and can be used for longer periods. To provide the user a comfortable operating position and to reduce strain, the distance between the handles is large. The handles and the short engine body mean the user always stands close to the machine, for easier handling and control.
- With the unique cut-n-break method you can work your way through the material step-by step at a low tool cost.
- Generously dimensioned miter gear provides high durability, minimal power loss and low noise levels.
- The long body and double cutting blades allow you to make cuts up to 16" deep.
- The adjustable blade guard allows close cutting to walls and floors.
- Provides starting with normal, slow acting fuses.
- The advanced electronic overload protection varies the rotation speed to warn of approaching overload.

TECHNICAL SPECIFICATION	
Engine	Electric 120V
Voltage	230 / 120 / 110V
Rated current, A	12/15/20 A
Power	1800 W
Rated input	2700/1800/2200 W
Blade diameter	9 inch
Max cutting depth	16 inch
Weight (excl. cutting equipment)	19.6 lbs
Weight incl. cutting equipment	22.9 lbs
Vibrations front handle	3.2 m/s ²
Vibrations rear handle	3.4 m/s ²
Sound power level, guaranteed (LWA)	109 dB(A)
Sound pressure level at operators ear	95 dB(A)

